7 dB quadrature squeezing at 860 nm with periodically poled KTiOPO₄

Shigenari Suzuki^{a)}

Department of Applied Physics, The University of Tokyo, 7-3-1 Hongo, Bunkyo-ku, Tokyo 113-8656, Japan; Advanced Communications Technology Group, National Institute of Information and Communications Technology (NICT), 4-2-1 Nukui-kitamachi, Koganei, Tokyo 184-8795, Japan; and Department of Electronics and Electrical Engineering, Keio University, 3-14-1 Hiyoshi, Kohoku-ku, Yokohama 223-8522, Japan

Hidehiro Yonezawa

Department of Applied Physics, The University of Tokyo, 7-3-1 Hongo, Bunkyo-ku, Tokyo 113-8656, Japan and CREST, Japan Science and Technology Agency, 1-9-9 Yaesu, Chuo-ku, Tokyo 103-0028, Japan

Fumihiko Kannari

Department of Electronics and Electrical Engineering, Keio University, 3-14-1 Hiyoshi, Kohoku-ku, Yokohama 223-8522, Japan

Masahide Sasaki

Advanced Communications Technology Group, National Institute of Information and Communications Technology (NICT), 4-2-1 Nukui-kitamachi, Koganei, Tokyo 184-8795, Japan and CREST, Japan Science and Technology Agency, 1-9-9 Yaesu, Chuo-ku, Tokyo 103-0028, Japan

Akira Furusawa

Department of Applied Physics, The University of Tokyo, 7-3-1 Hongo, Bunkyo-ku, Tokyo 113-8656, Japan and CREST, Japan Science and Technology Agency, 1-9-9 Yaesu, Chuo-ku, Tokyo 103-0028, Japan

(Received 10 April 2006; accepted 26 June 2006; published online 10 August 2006)

The authors observed -7.2 ± 0.2 dB quadrature squeezing at 860 nm by using a subthreshold continuous-wave pumped optical parametric oscillator with a periodically poled KTiOPO₄ crystal as a nonlinear optical medium. The squeezing level was measured with the phase of homodyne detection locked at the quadrature. The blue light induced infrared absorption was not observed in the experiment. © 2006 American Institute of Physics. [DOI: 10.1063/1.2335806]

Squeezed states of optical fields are important resources for photonic quantum information technology particularly with continuous variables.^{1–9} The performance of such protocols is limited directly by the squeezing level.^{1,10} For example, the fidelity in *n* cascaded quantum teleportation of coherent states scales as

$$F(n,r) = 1/(1 + ne^{-2r}),$$
(1)

with r the squeezing degree.^{2,11,12} The amount of information extracted by quantum dense coding must increase as

$$I(n_{s}, r) = \ln[1 + n_{s}e^{2r}],$$
(2)

where n_s is the average photon number used for signal modulation.^{5,7}

The highest squeezing level observed so far under a practical setting with the phase locked was -6.0 ± 0.3 dB by Polzik *et al.*¹³ They employed a continuous-wave (cw) Ti:sapphire laser at 852 nm and a subthreshold degenerate optical parametric oscillator (OPO) with a KNbO₃ crystal as a nonlinear optical medium. Since then this scheme has been a sort of standard in squeezing experiments at this wavelength range.

For KNbO₃, however, the pump blue light induced infrared absorption (BLIIRA) has been known as the limiting factor for attaining higher squeezing. A breakthrough was brought by Aoki *et al.*, ¹⁴ using periodically poled KTiOPO₄ (PPKTP). Although existences of the pump light induced absorption in KTiOPO₄ and PPKTP crystals had already been reported in pulsed light experiments,¹⁵ BLIIRA was not observed at 946 nm in their cw experiment.¹⁴

In this letter, we report the higher level of squeezing, -7.2 ± 0.2 dB, generated with PPKTP at 860 nm in cw experiment with the phase locked. This squeezing level opens potential applications to new coding in a single mode bosonic channel and sensing technologies.^{5,16,17} Particularly, it is expected to beat the Holevo capacity limit if the state purity is improved by reducing the present antisqueezing level because the squeezing level itself already exceeds the theoretical criterion of -6.78 dB.⁵ The size and performance of photonic quantum circuit will also be improved. For example, in the quantum teleportation of coherent states, either five cascaded processes or a single process with a high fidelity of 0.84 could be performed in principle. Furthermore, the wavelength range corresponds to the Cs D_2 line (852 nm), and hence fascinating for applications for controlling Cs atoms with nonclassical light.

A schematic of our experimental apparatus is shown in Fig. 1. A continuous-wave Ti:sapphire laser (Coherent MBR-110) at 860 nm is employed to accomplish this experiment. The beam from the Ti:sapphire laser is phase modulated at 15.3 MHz by an electro-optic modulator after passing an optical isolator. The modulation is utilized to lock a cavity for frequency doubling and a mode cleaning cavity with conventional FM-sideband locking technique.¹⁸

A part of the beam of around 900 mW is introduced into the frequency doubler to generate second harmonic at 430 nm as a pump beam for an OPO. The frequency doubler has a KNbO₃ crystal as a nonlinear optical medium in the

89. 061116-1

^{a)}Electronic mail: s-suzuki@nict.go.jp

^{0003-6951/2006/89(6)/061116/3/\$23.00}

^{© 2006} American Institute of Physics

Downloaded 11 Aug 2006 to 133.11.68.15. Redistribution subject to AIP license or copyright, see http://apl.aip.org/apl/copyright.jsp



FIG. 1. (Color online) Experimental setup. ISO: optical isolator, EOM: electro-optic modulator, AOM: acousto-optic modulator, SHG: second harmonic generator (frequency doubler), OPO: subthreshold degenerate optical parametric oscillator, MCC: mode cleaning cavity, HBS: 50:50 beam splitter, PTs: partial transmittance mirrors, HD: balanced homodyne detector, PDs: photodetectors, and PZTs: piezoelectric transducers.

external cavity with a bow-tie-type ring configuration. An output power from the doubler at 430 nm is more than 400 mW.

The OPO consists of a bow-tie-type ring cavity and a PPKTP crystal (Raicol Crystals). The cavity has the folding angle of 7° , two spherical mirrors (radius of curvature: 50 mm), and two plain mirrors. One of the plain mirrors is a partial transmittance mirror and works as the output coupler while the others are high reflectance mirrors. The round-trip length of 500 mm, the distance between the two spherical mirrors of 58 mm, and the PPKTP crystal (10 mm long) placed between the spherical mirrors result in waist radii of 20 μ m inside the crystal and 200 μ m outside the crystal. The cavity is mechanically stabilized by concatenating mirror mounts of the mirrors with aluminum plates. The OPO easily oscillates with the pump power of 200 mW, while the oscillation threshold $P_{\rm th}$ =181 mW is theoretically obtained from a nonlinear coefficient of the crystal of $E_{\rm NL}$ =0.023 W⁻¹, an intracavity loss L=0.006, and a transmittance of the output coupler of T=0.123 with the formula $P_{\rm th} = (T + L)^2 / 4E_{\rm NL}.$

The resonant frequency of the OPO cavity is locked using a "lock beam" and a photodetector (PD2) in Fig. 1 via the conventional FM-sideband locking technique.¹⁸ In order to avoid interference of the lock beam and a "probe beam" in Fig. 1, the beams are in opposite circulations of the cavity. Despite the effort, a fraction of the lock beam circulates backward because of reflection from surfaces of the crystal. This problem is solved by changing the transverse mode and the frequency of the lock beam.¹³ The transverse mode is changed from TEM₀₀ to TEM₁₀ by inserting a glass plate into a spatial half part of the beam. The frequency is shifted by about -120 MHz with an acousto-optic modulator. Thus the probe beam in TEM_{00} mode and the lock beam in TEM_{10} mode resonate simultaneously with the OPO cavity.

The generated squeezed light is combined with a local oscillator (LO) at a 50:50 beam splitter (HBS) and detected by a balanced homodyne detector (HD) with Si photodiodes (Hamamatsu S3590-06 with special antireflection coating). The circuit noise level of the homodyne detector at 1 MHz is



FIG. 2. (Color online) Power levels of quantum noise. (a) Shot noise level. (b) LO phase is locked at the squeezed quadrature. (c) LO phase is locked at the antisqueezed quadrature. (d) LO phase is scanned. These are normalized to make the shot noise level 0 dB. All traces except for (d) are averaged 20 times.

-18.5 dB below the shot noise level with the LO of 3 mW. An output of the HD is measured for the sideband component at 1 MHz by a spectrum analyzer (Agilent E4402B). The spectrum analyzer is set to the zero-span mode at 1 MHz with 30 kHz resolution bandwidth and 300 Hz video bandwidth.

A relative phase between the LO and the squeezed light is locked by use of the probe beam. The probe is locked in phase so that it is minimized/maximized along with the parametric gain of the OPO, and then works as a marker of the squeezed/antisqueezed quadrature of the squeezed light. As shown in Fig. 1, it is modulated in phase at 64 kHz by a piezoelectric transducer (PZT4), amplified or deamplified in the OPO, and then detected the fraction of 1% by a photodetector (PD4). The phase modulation at 64 kHz is used for two controllers based on the FM-sideband locking technique.¹⁸ An output signal of the PD4 is monitored by one of the controllers which locks the probe via controlling a piezoelectric transducer (PZT5). Then, a relative phase between the probe and the LO is locked by the other controller which monitors an interference signal of these beams from the HD and controls another piezoelectric transducer (PZT6). A fluctuation of the relative phase between the LO and squeezed light is estimated as $\theta = 3.9^{\circ}$, which is obtained via measuring rms values of error signals from the control circuits.

In order to improve the homodyne efficiency, the LO is spatially filtered by the mode cleaning cavity which yields the same spatial mode as the OPO output. The overall detection efficiency $\eta = \eta_P \eta_H$ after the OPO is obtained from the propagation efficiency of the optical path of $\eta_P = 0.99$ and the homodyne efficiency $\eta_H = 0.98$. The homodyne efficiency is dominated by the visibility between the LO and the OPO output mode because the quantum efficiency of the Si photodiodes could be treated as unity at the wavelength.

In addition, the alignment beam shown in Fig. 1 is an auxiliary beam which is reserved for use in alignment of constructing the cavity, measuring the intracavity loss, and matching the spatial mode of the pump beam with the OPO cavity. For the last application listed above, the alignment beam is converted to the second harmonic with the OPO as a Downloaded 11 Aug 2006 to 133.11.68.15. Redistribution subject to AIP license or copyright, see http://apl.aip.org/apl/copyright.jsp



FIG. 3. (Color online) Squeezing and antisqueezing levels at several powers of the pump beam. Plots with \times indicate measured values while \bigcirc and \triangle indicate theoretical ones which are calculated from measured classical parametric gains. The phase fluctuation of the LO is taken into account for the plots with \triangle while it is not done for those with \bigcirc . The inset shows purities calculated from the observed squeezing and antisqueezing levels using the definition Tr{ $\hat{\rho}^2$ } where $\hat{\rho}$ denotes the density operator of the observed state.

reference beam for the alignment.¹³ The reference beam propagates in the opposite direction to the pump beam and represents the OPO cavity mode. By matching the spatial mode of the reference beam with that of the pump beam, the pump beam is matched with the OPO cavity mode. In order to attain it, a triangle cavity in the path of the pump beam is utilized.¹³

Observed quantum noise levels of the OPO output are shown in Fig. 2. They were observed when the pump power was 100 mW. We succeeded in locking the LO phase at the squeezed and antisqueezed quadratures and in obtaining -7.2 ± 0.2 dB squeezing and $+11.6\pm0.2$ dB antisqueezing. The squeezing level of the generated state is estimated to be -7.5 dB by taking into account the effect of the circuit noise.

Note that the intracavity loss L=0.006 of the OPO stayed constant independently of the pump beam power, i.e., BLIIRA was not observed. Considering the existence of the pump light induced infrared absorption in experiments with pulsed lasers,¹⁵ we infer that the absence of BLIIRA in our experiment is due to the cw operation.

The pump power dependences of the squeezing and antisqueezing levels are shown in Fig. 3. The observed squeezing level saturates while the pump power increases. This fact could be due to the fluctuation $\tilde{\theta}$ which had a large effect on the observed squeezing level through mixing of the highly antisqueezed quadrature. Taking account of $\overline{\theta}$, the theoretical squeezing level R'_{-} and antisqueezing level R'_{+} are calculated as follows:¹⁹

$$R'_{\pm} \approx R_{\pm} \cos^2 \theta + R_{\mp} \sin^2 \theta, \qquad (3)$$

where R_{\pm} is modeled in Refs. 13 and 20. Considering $\tilde{\theta}=3.9^{\circ}$, the theoretical results almost agree with the experimental ones as shown in Fig. 3. Assuming $\tilde{\theta}=0$, the squeezing level would be -9.3 dB with 100 mW pumping.

In conclusion, we achieved -7.2 ± 0.2 dB quadrature squeezing at 860 nm with the phase locked at the maximally squeezed quadrature. Moreover, BLIIRA was not observed in a PPKTP crystal for the case of the cw pumped subthreshold optical parametric oscillator. The resulting state is expected to be utilized to perform various kinds of quantum information processing, to implement precise measurements, and to investigate the photon-atom interactions with Cs atoms.

One of the authors (S.S.) is grateful to Nobuyuki Takei for his experimental support. This work was partly supported by the MPHPT and the MEXT of Japan.

- ¹S. L. Braunstein and H. J. Kimble, Phys. Rev. Lett. **80**, 869 (1998).
- ²A. Furusawa, J. L. Sørensen, S. L. Braunstein, C. A. Fuchs, H. J. Kimble, and E. S. Polzik, Science **282**, 706 (1998).
- ³M. Ban, J. Opt. B: Quantum Semiclassical Opt. 1, L9 (1999).
- ⁴M. Ban, Phys. Lett. A **276**, 213 (2000).
- ⁵S. L. Braunstein and H. J. Kimble, Phys. Rev. A **61**, 042302 (2000).
- ⁶X. Li, Q. Pan, J. Jing, J. Zhang, C. Xie, and K. Peng, Phys. Rev. Lett. **88**, 047904 (2002).
- ⁷T. C. Ralph and E. H. Hutington, Phys. Rev. A **66**, 042321 (2002).
- ⁸W. P. Bowen, N. Treps, B. C. Buchler, R. Schnabel, T. C. Ralph, H.-A.
- Bachor, T. Symul, and P. K. Lam, Phys. Rev. A **67**, 032302 (2003).
- ⁹J. Mizuno, K. Wakui, A. Furusawa, and M. Sasaki, Phys. Rev. A **71**, 012304 (2005).
- ¹⁰N. Takei, H. Yonezawa, T. Aoki, and A. Furusawa, Phys. Rev. Lett. **94**, 220502 (2005).
- ¹¹S. L. Braunstein, C. A. Fuchs, and H. J. Kimble, J. Mod. Opt. **47**, 267 (2000).
- ¹²K. Hammerer, M. M. Wolf, E. S. Polzik, and J. I. Cirac, Phys. Rev. Lett. 94, 150503 (2005).
- ¹³E. S. Polzik, J. Carri, and H. J. Kimble, Appl. Phys. B: Photophys. Laser Chem. 55, 279 (1992).
- ¹⁴T. Aoki, G. Takahashi, and A. Furusawa, Opt. Express 14, 6930 (2006).
- ¹⁵S. Wang, V. Pasiskevicius, and F. Laurell, J. Appl. Phys. **96**, 2023 (2004).
- ¹⁶E. S. Polzik, J. Carri, and H. J. Kimble, Phys. Rev. Lett. **68**, 3020 (1992).
- ¹⁷C. M. Caves, Phys. Rev. D **23**, 1693 (1981).
- ¹⁸R. W. P. Drever, J. L. Hall, F. V. Kowalski, J. Hough, G. M. Ford, A. J. Munley, and H. Ward, Appl. Phys. B: Photophys. Laser Chem. **31**, 97 (1983).
- ¹⁹T. C. Zhang, K. W. Goh, C. W. Chou, P. Lodahl, and H. J. Kimble, Phys. Rev. A **67**, 033802 (2003).
- ²⁰M. J. Collett and C. W. Gardiner, Phys. Rev. A 30, 1386 (1984).